

- ◆ High Efficiency Plate Heat Exchanger
- ◆ Up to 80% Efficiency
- ◆ Reliable—No Moving Parts
- ◆ Cross or Parallel flow patterns
- ◆ Sanitary Drain Pan—No Standing Water

MODEL HX_M- (e)	f <sup>3</sup> /m	DIMENSIONS (In) (a)				FILTERS (a)	WEIGHT (a)
		L	W	H	Duct	Qty - Size (In)	lb
4A0202	500	19	26	47	10x20	1-10x20x2	335
4A0302	750	19	37	51	12x20	1-12x20x2	452
4A0204	1,000	34	26	59	16x20	1-16x20x2	564
4A0304	1,500	34	37	59	16x32	2-16x16x2	716
4A0404	2,000	34	47	59	16x40	2-16x20x2	859
4A0504	2,500	34	58	60	16x50	2-16x25x2	1,018
4A0406	3,000	49	47	76	24x40	2-24x20x2	1,274
4A0506	3,750	49	58	76	24x50	3-20x20x2	1,485
4A0606	4,500	49	69	76	24x60	3-20x24x2	1,695
4A0706	5,250	49	79	76	24x72	3-24x24x2	1,894
4A0608	6,000	64	69	88	30x64	6-16x20x2	2,240
4A0708	7,000	64	79	86	28x75	6-14x25x2	2,472
4A0808	8,000	64	90	94	32x80	8-16x20x2	2,835
4A0810	10,000	79	90	110	40x80	8-20x20x2	3,610
4A0812	12,000	94	90	126	48x72	8-18x24x2	4,483
4A0814	14,000	109	90	130	50x84	12-25x14x2	5,346
4A0816	16,000	124	90	150	60x80	8-30x20x2	6,247

(a) Weight and Dimensions are subject to change without notice

(e) Insert "I" for indoor or "O" for outdoor construction. Example HXIM or HXOM

